

REMARKS

Entry of the amendments to the specification, claims and abstract before examination of the application is respectfully requested. These claims have been amended to remove multiple dependencies and patentably define over the art of record.

If there are any questions regarding this Preliminary Amendment or the application in general, a telephone call to the undersigned would be appreciated since this should expedite the prosecution of the application for all concerned.


If necessary to effect a timely response, this paper should be considered as a petition for an Extension of Time sufficient to effect a timely response, and please charge any deficiency in fees or credit any overpayments to Deposit Account No. 05-1323 (Docket # 095309.57664US).

May 4, 2006

CROWELL & MORING LLP
Intellectual Property Group
P.O. Box 14300
Washington, DC 20044-4300
Telephone No.: (202) 624-2500
Facsimile No.: (202) 628-8844
GRE:aw

2762491

Respectfully submitted,


Gary R. Edwards
Registration No. 31,824

~~DaimlerChrysler AG~~

~~Threaded plate~~
THREADED PLATE

5

BACKGROUND AND SUMMARY OF THE INVENTION

This application is a National Phase of
PCT/EP2004/012377, filed November 2, 2004, and claims
10 the priority of German patent document DE 103 51 446.5,
filed November 4, 2003, the disclosure of which is
expressly incorporated by reference herein.

The invention relates to a threaded plate ~~according to~~
15 ~~the precharacterizing clause of claim 1~~ component
having a planar face with at least one threaded sleeve
extending from the base.

It is known to use threaded plates in vehicle body
20 construction ~~in order~~, for example, to fix door hinges
or closing brackets thereon. However, after [[some]]
time settling ~~phenomena~~ may occur ~~which are caused~~, for
example, [[by]] because the threaded plates ~~only being~~
are supported in a spotwise manner, and, in at discrete
25 points. In the case of vehicle doors, such setting may
lead to undesirable noises or to [[an]] unfavorable
closing behavior. The threaded plate is usually ~~fitted~~
installed and subsequently a conventional catalytic
dip-coating of the vehicle body parts is carried out,
30 [[which]] that is used to apply a first coating layer
which protects against corrosion and forms a key. One
reason for the spotwise support may be what are
referred to as buds which may lead to settling
phenomena if the installed threaded plate sticks to a
35 bearing surface. If, however, the threaded plate is
[[only]] fitted only in a later assembly ~~process~~ step,
after the dip-coating of the vehicle body parts, ~~this~~
~~makes its~~ fitting becomes more difficult and, in
addition to additional holders, also requires [[an]]

additional ~~outlay on personnel~~ labor.

[[The]] One object of the invention, therefore, is to
provide ~~is based on the object of providing~~ a threaded
5 plate in which the planar support of a planar basic
body is improved and which can be processed in a
~~production friendly~~ production-efficient manner.

~~The object is achieved according to the invention by~~
10 ~~the features of claim 1.~~

[[The]] This and other objects and advantages are
achieved by the threaded plate according to the
invention, which comprises a planar basic body
15 [[which]] that has at least one spacer element
protruding at an angle. The spacer element is provided
for bearing against a bearing surface[[. When]]; when
installed, it can prevent the threaded plate from
sticking during a conventional catalytic dip-coating of
20 a vehicle body, since the planar basic body can be kept
at a defined distance from a bearing surface. The
planar basic body comes into the bearing position when
a component is screwed to the threaded plate, and the
~~planar basic body~~ is drawn by its supporting region
25 onto the bearing surface by tightening a screw ~~being~~
~~tightened~~. In the process, the spacer element, which
protrudes at an angle, is forced into a flatly aligned
position. The distance between threaded plate and
bearing surface is overcome, and the threaded plate
30 bears with the planar basic body against the bearing
surface.

This arrangement essentially avoids settling phenomena
occurring later. [[A]] The manufacturing manufacture,
35 for example of B-pillars of a vehicle body, on which
door hinges and/or lock strikers are to be fixed by
means of threaded plates, is improved. The threaded

plate can be installed in a production-friendly manner before a dip-coating step. The installation of the threaded plate is simplified, and a ~~saving on costs~~ cost saving is achieved by omitting additional holders
5 ~~is possible~~.

If the spacer element is arranged in the edge region of the planar basic body, it can be used similarly to a holder[. This]], which facilitates the assembly of the
10 threaded plate. The spacer element can advantageously be integral with the threaded plate and can be formed during production of the threaded plate.

If the spacer element is connected to the planar basic
15 body by a predetermined buckling point, a bending movement is facilitated[. Less]], and force is required in [[order]] to change the angular position of the spacer element. The supporting surface of the planar basic body remains essentially level and can
20 later form a planar contact with a bearing surface. Tightening a screw is likewise facilitated by a relatively small force opposing a bending of the spacer element back into a flat position.

25 If the predetermined buckling point is to have a smaller material thickness than the planar basic body, it can be produced at reasonable cost by a simple notching or stamping operation.

30 If the spacer element protrudes from the planar basic body at a flat angle, a sufficient distance of the planar basic body from a bearing surface is ensured. At the same time, the supporting region of the planar basic body of the threaded plate is still essentially
35 level, so that the threaded plate protrudes at a sufficient distance from the bearing surface to prevent bonds, and the installation of the threaded plate is

not obstructed. The spacer element is preferably angled in the direction of the side which lies opposite the threaded sleeve. However, depending on the intended use, it is also ~~conceivable~~ possible for the spacer
5 element to be angled in the same direction as the threaded sleeve.

If the spacer element is designed as a yoke with two webs and a cross strut connecting the webs, it can be
10 used during installation for better adjustment and handling. Furthermore, the predetermined buckling point can be arranged in the webs, ~~with the result~~ so that the latter can easily be angled in one direction, and [[can be]] bent back again in the opposite direction.
15 The spacer element ~~can optionally~~ may also be designed as an angled tab which is arranged in the bearing surface of the planar basic body.

The cross strut preferably forms a contact surface. ~~The cross strut, and~~ initially bears with an edge against the bearing surface. The ~~distance made possible as a result~~ resulting separation between planar basic body and bearing surface prevents the threaded plate from sticking during dip-coating.
20

25 If the planar basic body has two opposite spacer elements between which the threaded sleeve is arranged, a symmetrical arrangement can be created. The threaded plate then [[only]] rests only against a bearing
30 surface on the spacer elements, or in each case one of the edges thereof.

If the planar basic body has two or more threaded sleeves, a single threaded plate can be used to arrange
35 a plurality of screw points on a vehicle body. The planar basic body thereby has a relatively large area and can be protected particularly favorably by the

spacer element against sticking during the dip-coating operation. The threaded sleeves are preferably arranged between two opposite spacer elements. A threaded plate is, therefore, provided, which is compact and can
5 easily be handled and, during installation, permits a defined distance between the planar basic body and the bearing surface ~~is therefore provided.~~

The principle of the invention as described can also be
10 used in an analogous manner in the case of other types of fixing.

~~Favorable refinements and advantages of the invention can be gathered from the description and the further~~
15 ~~claims.~~

~~The invention is explained in more detail below with reference to an exemplary embodiment which is described in the drawing, in which.~~

20 Other objects, advantages and novel features of the present invention will become apparent from the following detailed description of the invention when considered in conjunction with the accompanying
25 drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 ~~shows, diagrammatically,~~ is a schematic
30 depiction of a B-pillar with installed threaded plate and door hinge[[,]];

Fig. 2 is a perspective view which shows a cut-out of
35 a preferred threaded plate with a predetermined buckling point[[,]]; and

Fig. 3 is a perspective view which shows a further preferred threaded plate with two threaded sleeves.

5 DETAILED DESCRIPTION OF THE DRAWINGS

Fig. 1 shows, diagrammatically, the function of a threaded plate component 1 according to the invention in a B-pillar 10 of a vehicle body on which, for example, a hinge of a vehicle door or a lock striker
10 for a vehicle door is to be fixed.

The threaded plate component 1 comprises a threaded sleeve 3 protruding from an essentially level supporting region 25 of a planar basic body 2[[,]]; the
15 planar basic body 2 having has, on both sides of the threaded sleeve 3, a respective spacer element 4 protruding at an angle to one side. The spacer element 4 protrudes from the planar basic body 2 at a flat angle of less than 20° and thus ensures that the planar
20 basic body 2 is at a distance from a bearing surface of the B-pillar 10. The threaded sleeve 3 protrudes to the side of the threaded plate 1 which is opposite the angled spacer element 4. A reinforcement 12 is provided within the B-pillar 10. The threaded plate 1 can be
25 connected moveably to a carrying plate 11. At the location of installation of the threaded plate 1, the B-pillar has a bearing surface 23 for the threaded plate 1 with a suitable opening 24 through which a screw 15 can be screwed into the threaded sleeve 3. A
30 fitting 13 which has a corresponding bore 14 is provided outside the B-pillar 10. The screw 15 is guided through the bore 14 and the opening 24 into the threaded sleeve 3 and is screwed down. When the screw 15 is tightened, the planar basic body 2 is drawn onto
35 the bearing surface 23, and the spacer elements 4 are pressed flat. The planar basic body 2 then bears extensively with its supporting region 25 against the

bearing surface 23, and the spacer elements 4 lie in a plane with the planar basic body 2.

Fig. 2 shows a cut-out of a preferred threaded plate 1.
5 A spacer element 4 is arranged on an edge of a planar basic body 2 and is connected to a supporting region 25 of the planar basic body 2 via a predetermined buckling point 5. The predetermined buckling point 5 has a smaller material thickness than the planar basic body
10 2. The spacer element 4 is designed as a yoke which is integrally formed on the supporting region 25 and has two webs 21, 22 and a cross strut 20 connecting the webs 21, 22. An edge 6 of the cross strut 20 forms a contact surface for the threaded plate 1 on a bearing
15 surface. A distance 7 is formed between a bearing surface and a rear side of the planar basic body 2.

Fig. 3 shows a further preferred threaded plate 1. In this case, a planar basic body 2 has two opposite
20 spacer elements 4 between which two threaded sleeves 3 are arranged. The spacer elements 4 and the two threaded sleeves 3 are arranged along a longitudinal extent 8 of the threaded plate 1. A supporting region 25 of the planar basic body 2 is constricted in its
25 width between the two threaded sleeves 3. Weight can therefore be saved. Furthermore, access for a welding gun is possible at the constriction. The spacer elements 4 are designed as yokes and are connected to a supporting region 25 of the planar basic body 2 via
30 predetermined buckling points 5.

The foregoing disclosure has been set forth merely to illustrate the invention and is not intended to be limiting. Since modifications of the disclosed
35 embodiments incorporating the spirit and substance of the invention may occur to persons skilled in the art, the invention should be construed to include everything

within the scope of the appended claims and equivalents
thereof.